



APEL CO., LTD. JAPAN

APEL UV-VIS Spectrophotometer

PD-3000UVe

High Precision UV-VIS Spectrophotometer



Simple to operate & Excellent value

High accuracy

High quality grating ensures high precision.

Connectivity with peripherals

Possible to connect with a PC and a printer.

Excellent value

High performance and affordability are combined.

Economy Model



PD-3000UV_e

High Precision UV-VIS Spectrophotometer

Specifications:

Wavelength Range	190 to 1100 nm
Wavelength Width	5nm
Wavelength Accuracy	±2nm
Wavelength Scale	1nm scale(readable)
Wavelength Repeatability	0.5nm
Optical system	Single beam, grating system 1200lines/mm
Stray light	≤0.2% T
Display	128 x 64 LCD Display
Photometric Range	-0.3 to 3ABS 0 to 200.0% T 0 to 9999C (0-9999F)
Drift	<0.002A
Detector	Silicon photocell
Light source	Tungsten Halogen lamp, Deuterium lamp
Auto Zero	Equipped
Standard Sample holder	4 positions, 10mm x10mm Square cuvette
Printer output	Parallel port
Data output	USB
Power Requirements	100-240VAC,50/60Hz
Dimensions	466mm(W)x 395mm(L)x 185mm(H)
Weight	Net 15.0kg (Main body)

Specifications and appearance are subject to change without notice.

Standard Accessories:

Description	Quantity
Glass square cuvette	1 box (4)
Quartz square cuvette	1 box (2)
Power cord	1 pc
Application software	1 set
(CD-ROM,USB key,USB cable,Software manual)	
Fuse (1A)	1 pc
Dust cover	1 pc
Instruction manual	1 copy



APEL CO., LTD. JAPAN

Website

<http://www.apel.co.jp>

Distributor